

TRACK LOADERS

▪ MTL325 ▪



mustangmfg.com

dirt, mud, sludge, ... BRING IT ON



- Rated operating capacity of 5,528 lbs. (at 50% tipping load) and bucket break out force of 8,669 lbs.

- Two-speed drive system utilizes high-torque, axial-piston motors with planetary final drives, providing low speed for power and high speed for travel.



- Dedicated undercarriage and rubber tracks provide flotation and balanced traction in muddy and wet environments.

- New-style control handles include push buttons for other hydraulic functions and pilot-operated joystick controls cut down on operator fatigue.
- Tilt-back ROPS/FOPS and large rear door provide easy access to the internal components and engine reducing downtime.



West Bend, WI USA
Tel: 262-334-9461
Fax: 262-338-7517

For more information on Mustang equipment, call our literature hotline at **800-628-0491** or visit our website: **mustangmfg.com**

A Per SAE J7818, ISO 14397

SPECIFICATIONS

	MTL325	
GENERAL SPECIFICATIONS	Approximate Operating Weight	11,244 lbs. (5090)
	A. Maximum Lift Height to Bucket Pin (mm)	126.1" (3205)
	B. Dump Height (mm)	95.7" (2430)
	C. Reach at Maximum Lift (mm)	38.8" (985)
	D. Dump Angle	37°
	E. Bucket Rollback at Ground Level (mm)	31°
	F. Length without Bucket (mm)	123.5" (3135)
	G. Length with Bucket (mm)	156.9" (3985)
	H. Ground Clearance (mm)	13.5" (345)
	I. Angle of Departure	30°
	J. Height to top of ROPS	91.3" (2320)
	K. Width without Bucket (mm)	73.2" (1860)
	L. Width with Bucket (mm)	86" (2134)
M. Front Clearance Radius w/Bucket (mm)	106" (2692)	
PERFORMANCE	Rated Operating Capacity ^A at 35% Tipping Load (kg)	2470 lbs. (1120)
	Rated Operating Capacity ^A at 50% Tipping Load (kg)	3528 lbs. (1600)
	Tipping Load (kg) (SAE J7818, ISO 14397)	7056 lbs. (3200)
	Breakout Force - Bucket (kN)	8669 lbf. (38.5)
	Breakout Force - Lift Arm (kN)	8547 lbf. (38.0)
	Fuel Tank (L)	28.5 gal. (108)
	Alternator	80 amp
ENGINE	Make/Model	Kubota / V3800 DI-T
	Displacement (L) / Cylinders	230 cu.in. (3.8) / 4
	Horsepower (kW) @ 2200 rpm	92 hp (68.3)
	Maximum Torque (Nm)	240 ft.-lbs. (325)
	Engine Oil (L)	14.0 qts. (10.2)
	Engine Coolant (L)	17.4 qts. (16.5)
UNDERCARRIAGE	Traction Motor / Traction Drive	Piston / Planetary
	Traction Braking	Hydraulic
	Drawbar Pull (kN)	13,766 lbf (61.2)
	Roller Type / Track Rollers per Side	Steel / 5
	Track Width (mm)	18" (457)
	Track Contact Length (mm)	63" (1598)
	Ground Pressure (kg/cm ²)	4.5 psi (0.31)
	Travel Speed - Low (kg/hr)	0-4.8 mph (0-7.8)
Travel Speed - High (kg/hr)	0-7.5 mph (0-12.0)	
HYDRAULICS	Operating Pressure (bar)	2988 psi (206)
	Auxiliary Hydraulic Flow - standard (L/min)	23.4 gpm (88.6)
	Auxiliary Hydraulic High-Flow - option (L/min)	40.1 gpm (151.7)
	Hydraulic Tank Capacity (L)	15.9 gal. (60.1)

REFERENCE DIAGRAMS

